



Contract Number:  
CE - 2397-19  
Q.M. - 1129-17

KX040-4R3A WEB QUOTE #1647310  
Date: 5/12/2020 9:28:00 AM  
-- Customer Information --  
Hudson, Buck  
Tyler County Pct. 4  
buckhudson81@gmail.com  
409-429-4286

Quote Provided By  
Beaumont Tractor Company, Inc.  
Kyle Lee  
4430 College St.  
Beaumont, TX 77707  
email: kyle@beaumonttractor.com  
phone: 4098663960

-- Standard Features --

-- Custom Options --



K Series KX040-4R3A  
\*\*\* EQUIPMENT IN STANDARD MACHINE \*\*\*

**FEATURES**

Eco Plus System  
Auto Idler  
Rubber Track Model  
ROPS/OPG (Top Guard, Level  
1) Air Conditioning Cab  
Suspension Seat  
Kubota 1 Hydraulic Pump Load  
Sensing System  
1 Variable Displacement Pump  
All Controls Hydraulic Pilot  
Controls  
Two Operating Pattern  
Selection System  
Accumulator  
Digital Control Panel  
Adjustment Flow Presets,  
Service Alerts  
Float Angle Blade w/ Bolt-on  
Cutting Edge  
360 Degree Full Rotation  
70 Degree Left, 55 Degree  
Right Boom Swing  
17.2 gpm Adjustable Auxiliary  
Hydraulic Port 1  
Auxiliary Hydraulic Diverter  
Valve  
Thumb Bracket and Relief  
Valves  
Five Second Quick Preheat  
System  
Key Switch Stop System  
Half Pitch Rubber Tracks  
Self Bleed Filter System  
Auto-Downshift Two Speed  
Travel System  
Swivel Negative Brake  
Travel Negative Brake  
Third Line

**ENGINE**

D1803 Kubota DI Turbo CRS Tier 4  
Diesel Engine  
3 Cylinder, 4 Cycle  
39.9 Net HP @ 2200 rpm

**OPERATIONAL**

**DIMENSIONS**  
Max Digging Depth 11' 2.7"  
Max Digging Radius @ Ground  
Level 17' 9"  
Max Vertical Digging Depth 7' 4.8"  
Max Dumping Height 12' 9.5"

**DOZER BLADE**

**DIMENSIONS**  
Width 66.9"  
Height 16.75"  
Lift Above Ground 15.17"  
Drop Below Ground 15.94"

**PERFORMANCE**

Digging Force @ Bucket (K787B)  
9,535 lbs.  
Digging Force @ Dipper Arm 4,112  
lbs.  
Travel Speed (Low) 1.8 mph  
Travel Speed (High) 3.1 mph  
Climbing Ability 36% / 20°  
Lift Capacity 4,080 lbs.  
Over Front  
Blade Grounded  
2.0 ft. Load Point Height  
8.0 ft. Load radius

**DIMENSIONS AND  
OPERATING WEIGHT**

KX040-4R3A, Rubber Tracks,  
Air Conditioned  
ROPS/OPG (Top Guard, Level  
1) Cab, Angle Dozer Blade  
Overall Length 16' 0.2"  
Overall Width 5' 6 9"  
Overall Height 8' 1.8"  
Operating Weight 9,856 lbs.\*  
Ground Clearance 12.9"  
\*Includes operator's weight,  
175 lbs.

KX040-4R3A Base Price: \$63,018.00

(1) 36" QUICK ATTACH DRAINAGE BUCKET K787B-36" QUICK ATTACH DRAINAGE BUCKET	\$1,182.00
(1) 24" QUICK ATTACH TRENCHING BUCKET K787B-24" QUICK ATTACH TRENCHING BUCKET	\$1,311.00
(1) QUICK COUPLER K7870A-QUICK COUPLER	\$948.00
(1) HYDRAULIC THUMB KIT K7810A-HYDRAULIC THUMB KIT	\$2,683.00
<b>Configured Price:</b>	<b>\$69,152.00</b>
<b>BUY BOARD Discount:</b>	<b>(\$16,598.48)</b>
<b>SUBTOTAL:</b>	<b>\$52,553.52</b>
1Yr KX040-4R3A Extended Warranty (3000 hrs.)	\$950.00
<b>Dealer Assembly:</b>	<b>\$127.50</b>
<b>Freight Cost:</b>	<b>\$635.00</b>
<b>PDI:</b>	<b>\$250.00</b>

Total Unit Price: \$54,518.02  
Quantity Ordered: 1  
Final Sales Price: \$54,518.02

**Purchase Order Must Reflect  
the Final Sales Price**

To order equipment - purchase orders must be made out and returned to:

Kubota Tractor Corporation  
Attn: National Accounts  
1000 Kubota Drive  
Grapevine, TX 76051  
or email NA.Support@kubota.com  
or call 817-758-1171 or fax 844-582-1501

\*All equipment specifications are as complete as possible as of the date on the quote. Additional attachments, options, or accessories may be added (or deleted) at the discretional price. All specifications and prices are subject to change. Taxes are not included. The PDI (fee and freight for attachments and accessories quote) may have additional charges added by the delivering dealer. These charges will be billed separately. Prices for product quoted are good for 60 days from the date shown on the quote. All equipment as quoted is subject to availability.

© 2018 Kubota Tractor Corporation. All rights reserved.

Send a copy of P.O. to Kyle

05/14/2020 11